



# PUNE ENERGY CONTROL DEVICES PVT. LTD.



OIL FILTRATION TROLLEY

Model Decoding

1	2	3	4	5	6	7	8	9	10
OFT	0	A	2	Y	1	B	010	00	1X

- 1 Oil Filtration Trolley : OFT
- 2 Standard : 0 Duplex : 00
- 3 Seal : A : NBR B : Viton
- 4 Flow : 1 : 20 LPM at 1440 RPM 2 : 40 LPM at 1440 RPM
- 5 Electric Motor : X : 1.1 Kw, 1440 RPM, Y : 1.5 Kw, 1440 RPM,
- 6 Filter Size : 1 : 330 Size 2 : 660 Size
- 7 Filter Material : B : Betamicron A : Aquamicron
- 8 Filtration Rating : 003  $\mu$ m Betamicron, 005  $\mu$ m Betamicron  
010  $\mu$ m Betamicron 020  $\mu$ m Betamicron  
040  $\mu$ m Aquamicron
- 9 Sensor : CS Contamination sensor 00 : Without Contamination Sensor
- 10 Design : 1X The latest version is always supplied



# PUNE ENERGY CONTROL DEVICES PVT. LTD.

## Technical Specifications

Type of Pump	Gear Pump
Max. Flow rate	20 LPM & 40 LPM
Operating Pressure	4 to 5 Bar
Permiss. Suction Pressure	-0.4 bar..... +0.6 bar
Viscosity Range	15 to 200 mm <sup>2</sup> /sec
Permiss. Operating Fluid	Mineral Oil (Other fluid on request)
Fluid Temp.	25.....80° C
Ambient Temp	25.....40° C
Seal	NBR
Length Of Electric Cable	6 Mtrs.
Length Of Hose	3 Mtrs
Hose Connection	To suit ¾" / 1" BSP connection

Hydraulic Circuit

